



Color Variants

RB492705
With fresh cooling close to 32 °F
Fully integrated, panel ready

Optional accessories

RA430100
Storage container with transparent lid, anthracite.
RA450022

Installation Accessories

RA421913
Stainless steel door panel with handles
RA423340
RA425110
Long stainless steel door handle
RA425910
Short stainless steel door handle
RA428913
Stainless steel door panels, handleless
RA460000
Installation kit for side-by-side installation (for connecting any two columns)
RA460012
RA460030
Connecting element for vertically split fronts (for fridge-freezer combination with one door)
RA464913
Ventilation grill, stainless steel

RB492705

Vario fridge-freezer combination 400 series

With fresh cooling close to 32 °F

Fully integrated, panel ready

Niche width 36" (91.4 cm)

Cooling section with one door and one fully extendable freezing drawer

Stainless steel interior with solid anthracite aluminium elements
Warm white and glare-free LED light spots

Opening assist for door with two options: 1. Push-to-open function for integration into handleless furniture front 2. Pull-to-open function to facilitate opening the door using a handle

Flat stainless steel inner door, full-length

Almost invisible rail system for shelves and door racks for flexible positioning
Solid anthracite aluminium door racks
1 fresh cooling drawer close to 32 °F with manually adjustable temperature and one fresh cooling drawer with manually adjustable humidity
Integrated automatic ice maker with fixed water connection
Fully extendable freezer drawer with practical divider in anthracite
TFT touch display
Net volume 19.5 ft3 cu.ft. (553) litres
Energy Star certified

Operation

TFT touch display operation.
Clear text display in 44 languages.

Technical Features

Dynamic cold air distribution with Multi-Flow Air System.
Automatic defrosting with defrost water evaporation.
Cushioned door closing system.
Activated charcoal air filter.
Sabbath mode certified by Star-K.
When rest mode is active, the appliance can only be opened using a handle.
Open-door and malfunction warning system.
Home network integration for digital services (Home Connect) wireless via WiFi.
The use of the Home Connect functionality depends on the Home Connect services, which are not available in every country. For further information please check: home-connect.com.

Cooling compartment

No-Frost technology with fast cooling.
Temperature adjustable from 35 °F to 46 °F.
3 safety glass shelves, white glass, 2 of which are individually adjustable in height.
4 brilliant LED light spots with warm white, glare-free light within cooling area and drawers.
Flat door rail system with fully flexible positioning of door racks.
3 height adjustable door bins, one of which is a large gallon door bin.
Net volume 397 l litres.

Fresh cooling close to 32 °F

1 fully extendable fresh cooling drawer close to 32 °F with transparent front, illuminated.
Cushioned closing system.
Temperature can be adjusted manually.
Ideal for meat, fish and poultry.
Net volume 0 litres.

Temperature controlled drawer

1 fully extendable fresh cooling drawer with transparent front, illuminated.
Cushioned closing system.

Product Features

Multi-Flow Air Tower

Yes

SUPERCOOL

Yes

SUPERFREEZE

No

Carbon Air Filter

No

Temperature Controlled Drawer

No

Humidity Control Drawer

No

Number of Door Bins - Refrigerator

3

Adjustable Door Bins - Refrigerator

No

Tilt-Out Door Bins - Refrigerator

No

Gallon Storage Bins

1

No. of shelves in fridge

3

Door Hinge

Right reversible

Adjustable Shelves - Refrigerator

2

Number of Shelves - Freezer

Reversible Door Hinge

Yes

Adjustable Shelves - Freezer

No

Consumption and connection features

UPC code

825225961000

Color / Material housing

Variant color

Not applicable

Panel ready

Not possible

Silence level (dBA)

42

Watts (W)

350

Current (A)

10

Volts (V)

110-120

Frequency (Hz)

60

Total annual energy consumption (kWh)

504.1

Energy Star® qualified

No

Approval certificates

CSA

Power Cord Length

139 1/3"

Required cutout size (HxWxD) (in)

84" x 36" x 24 3/4"

Appliance Width (in)

35 3/4"

Height (in)

83 3/4 "

Depth (in)

24"

Capacity in 0.75l (bordeaux bottles)

Total unit gross capacity (cu. ft.) - AHAM

19.5

Product packaging dimensions

(HxWxD) (in)

89.37 x 29.33 x 39.37

Refrigerator Gross capacity (cu. ft.)

14.0

Freezer Gross capacity (cu ft)

6

Net weight (lbs)

446.000

Gross weight (lbs)

489.000

SKU

RB492705

2020-11-04

Page 1

Humidity can be adjusted manually.
Ideal for fruit and vegetables.

Freezer compartment

No-frost technology with fast freezing at -22 °F.
Temperature adjustable from 3 °F to -11 °F.
4-star freezer compartment.
Freezing capacity 7.8 kg/24 h.
Interior lighting with 2 LED light spots, warm white light.

Ice dispenser

Integrated automatic ice maker in the freezer compartment, with fixed water connection.
Particle filter for water inlet, integrated in ventilation grille area.
Saturation indicator shown in TFT touch display.
Ice maker can be switched off independently.
Ice cube production approx. 2.9 lb (1.3 kg)/24 h.
Removable ice storage container with approx. 6.6 lbs. (3 kg) capacity.

Consumption data

Energy consumption 504.08 kWh/year.
Noise level 42 dB (re 1 pW).

Planning notes

Flat hinge.
Door hinge right, reversible.
Door opening angle of 115°, fixable at 90°.
Max. door panel weight: Door 103 lbs (47 kg). Drawer 22 lbs (10 kg).
Shut-off valve for water connection must be planned next to the appliance and always be accessible.
If the water pressure exceeds 116 psi, connect pressure relief valve between water tap and hose set.

Rating

Total rating 1.079 kWh/24 h.
Total Amps: 10 A.
Connecting cable 118" (3.0 m), detachable.
Cold water connection required.
Electrical location 6" above ground in lower left corner of unit.
Supply hose 51,1 INCH (1.3 m) with 1/4" male compression fitting (standard icemaker connector).
Water pressure 29 to 116 psi.

GAGGENAU

RB492705
Vario fridge-freezer combination 400 series
With fresh cooling close to 32 °F
Fully integrated, panel ready
Niche width 36" (91.4 cm)
Cooling section with one door and one fully extendable freezing drawer
2020-11-04
Page 2

